




varioPRINT 140 SERIES

MONOCHROME PRODUCTION DIGITAL PRESSES

PRODUCT SPECIFICATIONS



varioPRINT 140 shown with optional accessories.

varioPRINT 140 SERIES PRODUCT SPECIFICATIONS

MAIN UNIT

Marking Engine

Technology:	DirectPress
Print Resolution:	
Engine:	600 x 2400 dpi, 200 lpi
PCL:	600 x 600 dpi
Adobe® PostScript® 3:	1200 x 1200 dpi (Enhanced), 600 x 2400 dpi
Max. Print Speed (ipm):	140/130/115 (Letter), 73/68/60 (11" x 17")
First-Copy-Out Time:	3.9 Seconds (Letter)

Paper Size

Maximum:	12.6" x 19.2" (320 mm x 488 mm)
Minimum:	5.5" x 7.2" (140 mm x 182 mm)

Standard Paper Capacity (iPIM): 4,000 Sheets (80 gsm)

2 x Bulk Tray:	1,500 Sheets (Letter, Statement ¹)
2 x Multisize Tray:	500 Sheets
Tray 3:	5.5" x 7.2" to 12.6" x 17"
Tray 4:	5.5" x 7.2" to 12.6" x 19.2"

Feeding (iPIM):	Friction-fed
Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm) (All trays)
Duplex:	Up to 300 gsm
Power Source:	208 V/20 A
Options:	Bulk Tray Small Format-A1

Duplex Color Image Reader-N1

Image Sensor:	CCD
Document Size:	Statement to 11" x 17"
Resolution:	Up to 600 x 600 dpi
Tray Capacity:	Up 200 Sheets (20 lb. Bond)
Paper Weight:	10 lb. Bond to 80 lb. Cover (38 gsm to 220 gsm)
Scan Speed	
BW:	Up to 130 ipm (300 x 300 dpi/600 x 600 dpi)
Color:	Up to 135 ipm (300 x 300 dpi) Up to 37 ipm (600 x 600 dpi)

INPUT ACCESSORIES

ePIM (External Paper Input Module) (Optional)

Feeding Technology:	Air Separation, Suction Feeding
Standard Paper Capacity:	4,600 Sheets (20 lb. Bond)
Tray 1 and 2:	600 Sheets
Tray 3 and 4:	1,700 Sheets
	3,400 Sheets (20 lb. Letter, with Duo Tray installed)
Maximum Capacity:	8,000 Sheets (20 lb. Bond) ²
Acceptable Size (All trays):	8" x 8" to 12.6" x 19.2"
Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm)
Power Source:	120 V/15 A
Options:	Duo Tray, Forms Assist Module II

Document Insertion Unit-N1

Tray Capacity	
Upper Tray:	Up to 200 Sheets (20 lb. Bond)
Lower Tray:	Up to 200 Sheets (20 lb. Bond)
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Paper Size: ³	11" x 17", 12" x 18", 13" x 19", LGL, LTR, LTR-R, EXEC, Custom Size (7.2" x 7.2" to 13" x 19.2")
Power Source:	120 V/15A

FINISHING ACCESSORIES

Staple Finisher-W1/Booklet Finisher-W1

Tray Capacity	
Top Tray:	Up to 1,000 Sheets (20 lb. Bond)
Lower Tray:	Up to 4,000 Sheets (20 lb. Bond)
Booklet Tray:	Up to 30 Booklets or Limitless
Staple Positions:	Corner Stapling, Double Stapling, Saddle ³
Paper Weight:	14 lb. Cover to 110 lb. Cover (52 gsm to 300 gsm)
Paper Size ⁴	
Stapling:	11" x 17", LGL, LTR-R, EXEC, LTR, Custom Size (8.3" x 11" to 13" x 19.2")
Booklet Finisher:	11" x 17", LGL, LTR-R, 12" x 18" Custom Size (8.3" x 11" to 11.7" x 17")
Stapling Capacity:	Up to 100 Sheets, Maximum (Letter) (20 lb. Bond)
Booklet Stapling Capacity	
Uncoated:	Up to 25 Sheets (20 lb. Bond/80 gsm)
Coated:	Up to 10 Sheets (28 lb. Bond/106 gsm)
V-Folding:	Up to 5 Sheets without Stitch
Power Source:	120 V/15 A

Puncher Unit-BS1

(Option for Finisher-W1/Booklet Finisher-W1)

Paper Weight:	13 lb. Bond to 73 lb. Cover (50 gsm to 200 gsm)
Paper Size	
2-Hole:	Legal, Letter-R
3-Hole:	11" x 17", Letter, Executive
Punch Speed:	Same as Speed of Marking Engine
Power Source:	From Main Unit

High Capacity Stacker-H1

Offset Stack Capacity:	Up to 6,000 Sheets (20 lb. Bond)
Top Tray Capacity:	Up to 200 Sheets (20 lb. Bond)
Paper Size: ⁴	5.5" x 7.2" to 13" x 19.2"
Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm)
Max. Connectivity:	2 Units
Power Source:	120 V/15 A

varioPRINT 140 SERIES PRODUCT SPECIFICATIONS (Continued)

Multi Function Professional Puncher-B1

Paper Weight	
Plain:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
Coated:	32 lb. Bond to 110 lb. Cover (118 gsm to 300 gsm)
Paper Size:	12" x 18", 11" x 17", 9" x 12", LTR, LGL, LTR-R, STMT
Die Set Patterns:	Loose Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Color Coil 44-Hole
Power Supply:	120 V/15 A

GBC eWire Pro⁵

Bound Book Size: ⁶	15 to 100 Sheets
Paper Size:	Letter, 5.5" x 8.5", Tab Stock
Paper Weight:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
Wire Choices:	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
Stack Capacity:	Up to 35 Books
Infeed:	Multi Function Professional Puncher-B1
Power Supply:	115 V, 60 Hz, 2.8A
Weight:	500 lb.
Dimensions (W x D x H):	35.8" x 31.3" x 42.6"

Booklet Trimmer-F1³

Margin Trimming:	Front-edge Trim
Trim Amount:	0.08" to 1.1"
Trim Thickness:	50 Sheets (25 Sheets Folded)
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Output Tray Capacity:	30 Booklets
Power Source:	From Booklet Finisher-W1

Two-Knife Booklet Trimmer-A1 (Optional for Booklet Trimmer-F1)

Margin Trimming:	Top and Bottom
Trim Amount:	0.08" to 0.59"
Trim Thickness:	50 Sheets (25 Sheets Folded)
Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Power Supply:	120 V/15 A

Paper Folding Unit-J1⁷

Double Parallel Fold:	Legal, Letter-R
C/Accordion Fold:	Letter-R
Z-Fold:	11" x 17"
Half-fold:	Letter-R
Supported Media Weights:	13 lb. Bond to 28 lb. Bond (50 gsm to 105 gsm)
Power Source:	From Finisher-W1/Booklet Finisher-W1

Decurler Unit-C1

Paper Weight:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
Paper Size:	5.5" x 7.2" to 13" x 19.2"

DFD Adapter and Finisher Bridge-A1⁸

Paper Weight:	13 lb. Bond to 110 lb. Cover (50 gsm to 300 gsm)
Connectivity:	745 mm Paper Path Height (Input), 860 mm Paper Output Path, CAN Connection, Requires Upper Tray from Finisher-W1 to be Removed and Replaced by the Finisher Bridge-W1
Requirements:	Staple/Booklet Finisher-W1
Power Supply:	From Finisher

MAX Ring Binder MB-1000C⁹

Binding Capacity: ⁶	2 to 100 Sheets
Sheet Size:	Letter, Letter Tab
Paper Weight:	17 lb. Bond to 80 lb. Cover (64 gsm to 216 gsm)
Ring Elements:	Small (Up to 50 Sheets), Large (Up to 100 Sheets)
Power Source:	120-127 V, 60 Hz, 2.8 A
Weight:	331 lb.
Dimensions (W x D x H):	55.5" x 26.8" x 41.8"

Plockmatic BLM50/35 Professional Booklet Maker⁹

Booklet Size: ⁶	Up to 50 Sheets
Paper Size:	8.1" x 10.8" to 12.6" x 18"
Paper Weight	
Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)

Trim Amount	
Face:	0.04" to 1"
Top/Bottom:	0.196" to 1.18"
Paper Rotating:	SDD Rotator RTM3550 required
Weight:	1,235.7 lb.
Dimensions (W x D x H): ¹⁰	86.2" x 28.8" x 41.4"

SDD Square Fold Booklet Maker¹¹

Booklet Capacity: ⁶	Up to 25 Sheets
Booklet Input Size:	4.71" x 8.27" to 9.6" x 12.6"
Booklet Output Size:	4.71" x 7.87" to 9.6" x 12.6"
Paper Weight:	16 lb. Bond to 110 lb. Cover
Trim Amount:	0.08" to 1.38"
Power Supply:	120 V, 60 Hz, 15 A
Weight:	154 lb.
Dimensions (W x D x H):	44.9" x 23.6" x 44.9"

varioPRINT 140 SERIES PRODUCT SPECIFICATIONS (Continued)

SDD Square Fold Booklet Maker with Two Knife Trim¹¹

Booklet Capacity: ⁶	Up to 25 Sheets
Booklet Input Size:	4.88" x 5.51" to 9.6" x 12.6"
Booklet Output Size:	4.88" x 5.51" to 9.6" x 12.6"
Paper Weight:	16 lb. Bond to 110 lb. Cover
Trim Amount:	0.08" to 1.38"
Power Supply:	120 V, 60 Hz, 15 A
Weight:	573 lb.
Dimensions (W x D x H):	62.7" x 27.6" x 51.2"

SDD BLM300C Professional Booklet Maker⁹

Booklet Size: ⁶	Up to 30 Sheets
Paper Size:	5.5" x 9.9" to 12.6" x 18.5"
Paper Weight:	
Body:	16 lb. Bond to 64 lb. Cover (60 gsm to 240 gsm)
Cover:	20 lb. Bond to 110 lb. Cover (80 gsm to 300 gsm)
Trim Amount ¹²	
Face:	0.08" to 0.63"
Top/Bottom:	0.08" to 1.38"
Paper Rotating: ¹³	8" x 8" to 9.1" x 12.6"
Weight:	1,477 lb.
Dimensions (W x D x H): ¹⁴	96.5" x 27.6" x 45.3"

PRINT SERVER

Processor:	2.7 GHz
Memory:	4 GB
Hard Drive:	500 GB
OS:	Windows 10 LTSC
Supported PDLs:	APPE ¹⁵ , PDF/PS, PCL, XPS ¹⁶ , PPML ^{16,17}
Standard:	Scheduler, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Remote Control
Optional:	DocBox, Color Scanning, Multiple Queues, Streaming, Accounting, Integrity Checker, E-Shredding, DP Link, KDK Link

¹ Requires Bulk Tray Small Format-A1.

² With Duo Tray option installed in Tray 3 and 4 of ePIM. Letter only in trays with Duo Tray option installed.

³ Requires Booklet Finisher-W1.

⁴ Maximum supported size for varioPRINT 140 Series engine is 12.6" x 19.2". Document Insertion Unit supports 13" x 19.2".

⁵ Requires Multi Function Professional Puncher-B1 and Decurler Unit-C1.

⁶ Based on 20 lb. Bond.

⁷ Requires Staple Finisher-W1 or Booklet Finisher-W1.

⁸ Requires Printer Software v6.1 or higher.

⁹ High Capacity Stacker-H1, DFD Interface Kit, and DFD Paper Path, or DFD Adapter and Finisher Bridge-A1 required.

¹⁰ Dimensions include Plockmatic BLM 50/35 Booklet-maker, Booklet Fold Module, and Trimmer.

¹¹ Booklet Finisher-W1 and Booklet Trimmer-F1 required.

¹² SDD Trimmer modules required.

¹³ SDD Rotator RTM6940 required.

¹⁴ Dimensions include SDD BLM 300C Booklet Maker, Face Trim, and Square Fold Modules.

¹⁵ Standard on varioPRINT 140/130. Optional on varioPRINT 115.

¹⁶ Optional.

¹⁷ Requires APPE.



USA.CANON.COM/PRODUCTIONPRINTING



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has qualified these models as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Canon and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. varioPRINT and PRISMA are registered trademarks of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. All output is simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.
©2021 Canon U.S.A., Inc. All rights reserved.

